

gcloud compute os-login ssh-keys add

Archived: 2026-04-29 07:32:01 UTC

gcloud compute os-login ssh-keys add Stay organized with collections Save and categorize content based on your preferences.

NAME

gcloud compute os-login ssh-keys add - add an SSH public key to an OS Login profile

SYNOPSIS

```
gcloud compute os-login ssh-keys add ( --key = KEY | --key-file = KEY_FILE ) [ --ttl = TTL ]  
[ GLOUD WIDE FLAG ... ]
```

DESCRIPTION

`gcloud compute os-login ssh-keys add` accepts either a string containing an SSH public key or a filename for an SSH public key and adds that key to the user's OS Login profile.

EXAMPLES

To add the key in `/home/user/.ssh/id_rsa.pub` to your OS Login profile, run:

See more code actions.

```
gcloud compute os-login ssh-keys add --key-file=/home/user/.ssh/id_rsa.pub
```

To add the same key, but with a one year expiration time, run:

See more code actions.

```
gcloud compute os-login ssh-keys add --key-file=/home/user/.ssh/id_rsa.pub --ttl=1y
```

To add a key not stored in a file, run:

```
gcloud compute os-login ssh-keys add --key='ssh-rsa AAAAB3NzaC1yc2EAAA...MTg+InRG47+/O4/uWE0y6gIQEF  
user@example.com'
```

REQUIRED FLAGS

Exactly one of these must be specified:

`--key` = *KEY*

The SSH public key to add to the OS Login Profile.

`--key-file` = *KEY_FILE*

The path to a file containing an SSH public key to add to the OS Login Profile.

OPTIONAL FLAGS

`--ttl` = *TTL*

The amount of time before the SSH key expires. For example, specifying `30m` will set the expiration time on the SSH key for 30 minutes from the current time. A value of 0 will result in no expiration time. See [\\$ gcloud topic datetimes](#) for information on duration formats.

GCLOUD WIDE FLAGS

These flags are available to all commands: [--access-token-file](#) , [--account](#) , [--billing-project](#) , [--configuration](#) , [--flags-file](#) , [--flatten](#) , [--format](#) , [--help](#) , [--impersonate-service-account](#) , [--log-http](#) , [--project](#) , [--quiet](#) , [--trace-token](#) , [--user-output-enabled](#) , [--verbosity](#) .

Run `$ gcloud help` for details.

NOTES

These variants are also available:

```
gcloud alpha compute os-login ssh-keys add
```

```
gcloud beta compute os-login ssh-keys add
```

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see the [Google Developers Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated 2025-05-07 UTC.

Source: <https://cloud.google.com/sdk/gcloud/reference/compute/os-login/ssh-keys/add>