

# Systeminfo

Archived: 2026-04-06 01:03:45 UTC

Displays detailed configuration information about a computer and its operating system, including operating system configuration, security information, product ID, and hardware properties, such as RAM, disk space, and network cards.

**systeminfo[.exe] [/s *Computer* [/u *Domain\User* [/p *Password*]]] [/fo {**TABLE**|**LIST**|**CSV**}] [/nh]**

**/s *Computer*** : Specifies the name or IP address of a remote computer (do not use backslashes). The default is the local computer.

**/u *Domain \ User*** : Runs the command with the account permissions of the user specified by *User* or *Domain\User*. The default is the permissions of the current logged on user on the computer issuing the command.

**/p *Password*** : Specifies the password of the user account that is specified in the **/u** parameter.

**/fo { **TABLE** | **LIST** | **CSV** }** : Specifies the format to use for the output. Valid values are **TABLE**, **LIST**, and **CSV**. The default format for output is **LIST**.

**/nh** : Suppresses column headers in the output. Valid when the **/fo** parameter is set to **TABLE** or **CSV**.

**/?** : Displays help at the command prompt.

The following examples show how you can use the **systeminfo** command:

**systeminfo.exe /s srvmain**

**systeminfo.exe /s srvmain /u maindom\hiropln**

**systeminfo /s srvmain /u maindom\hiropln /p p@ssW23 /fo table**

Format	Meaning
<i>Italic</i>	Information that the user must supply
<b>Bold</b>	Elements that the user must type exactly as shown
Ellipsis (...)	Parameter that can be repeated several times in a command line

<b>Format</b>	<b>Meaning</b>
Between brackets ([ ])	Optional items
Between braces ({}); choices separated by pipe ( ). Example: {even odd}	Set of choices from which the user must choose only one
Courier font	Code or program output

[Command-line reference A-Z](#)

---

Source: <https://technet.microsoft.com/en-us/library/bb491007.aspx>