

pam_unix(8) - Linux man page

Archived: 2026-04-05 23:51:54 UTC

Name

pam_unix - Module for traditional password authentication

Synopsis

pam_unix.so [...]

Description

This is the standard Unix authentication module. It uses standard calls from the system's libraries to retrieve and set account information as well as authentication. Usually this is obtained from the `/etc/passwd` and the `/etc/shadow` file as well if shadow is enabled.

The account component performs the task of establishing the status of the user's account and password based on the following *shadow* elements: `expire`, `last_change`, `max_change`, `min_change`, `warn_change`. In the case of the latter, it may offer advice to the user on changing their password or, through the `PAM_AUTHTOKEN_REQD` return, delay giving service to the user until they have established a new password. The entries listed above are documented in the [shadow\(5\)](#) manual page. Should the user's record not contain one or more of these entries, the corresponding *shadow* check is not performed.

The authentication component performs the task of checking the users credentials (password). The default action of this module is to not permit the user access to a service if their official password is blank.

A helper binary, [unix_chkpwd\(8\)](#), is provided to check the user's password when it is stored in a read protected database. This binary is very simple and will only check the password of the user invoking it. It is called transparently on behalf of the user by the authenticating component of this module. In this way it is possible for applications like [xlock\(1\)](#) to work without being `setuid-root`. The module, by default, will temporarily turn off `SIGCHLD` handling for the duration of execution of the helper binary. This is generally the right thing to do, as many applications are not prepared to handle this signal from a child they didn't know was `fork()`d. The `noreap` module argument can be used to suppress this temporary shielding and may be needed for use with certain applications.

The password component of this module performs the task of updating the user's password.

The session component of this module logs when a user logins or leave the system.

Remaining arguments, supported by others functions of this module, are silently ignored. Other arguments are logged as errors through [syslog\(3\)](#).

Options

debug

Turns on debugging via [syslog\(3\)](#).

audit

A little more extreme than debug.

nullok

The default action of this module is to not permit the user access to a service if their official password is blank. The **nullok** argument overrides this default.

try_first_pass

Before prompting the user for their password, the module first tries the previous stacked module's password in case that satisfies this module as well.

use_first_pass

The argument **use_first_pass** forces the module to use a previous stacked modules password and will never prompt the user - if no password is available or the password is not appropriate, the user will be denied access.

nodelay

This argument can be used to discourage the authentication component from requesting a delay should the authentication as a whole fail. The default action is for the module to request a delay-on-failure of the order of two second.

use_authtok

When password changing enforce the module to set the new password to the one provided by a previously stacked **password** module (this is used in the example of the stacking of the **pam_cracklib** module documented below).

not_set_pass

This argument is used to inform the module that it is not to pay attention to/make available the old or new passwords from/to other (stacked) password modules.

nis

NIS RPC is used for setting new passwords.

remember=*n*

The last *n* passwords for each user are saved in /etc/security/opasswd in order to force password change history and keep the user from alternating between the same password too frequently.

shadow

Try to maintain a shadow based system.

md5

When a user changes their password next, encrypt it with the MD5 algorithm.

bigcrypt

When a user changes their password next, encrypt it with the DEC C2 algorithm.

sha256

When a user changes their password next, encrypt it with the SHA256 algorithm. If the SHA256 algorithm is not known to the [crypt\(3\)](#) function, fall back to MD5.

sha512

When a user changes their password next, encrypt it with the SHA512 algorithm. If the SHA512 algorithm is not known to the [crypt\(3\)](#) function, fall back to MD5.

blowfish

When a user changes their password next, encrypt it with the blowfish algorithm. If the blowfish algorithm is not known to the [crypt\(3\)](#) function, fall back to MD5.

rounds=*n*

Set the optional number of rounds of the SHA256, SHA512 and blowfish password hashing algorithms to *n*.

broken_shadow

Ignore errors reading shadow information for users in the account management module.

Invalid arguments are logged with [syslog\(3\)](#).

Module Types Provided

All module types (**account**, **auth**, **password** and **session**) are provided.

Return Values

PAM_IGNORE

Ignore this module.

Examples

An example usage for /etc/pam.d/login would be:

```
# Authenticate the user
auth    required  pam_unix.so
# Ensure users account and password are still active
account required  pam_unix.so
# Change the users password, but at first check the strength
# with pam\_cracklib\(8\)
password required pam_cracklib.so retry=3 minlen=6 difok=3
password required pam_unix.so use_authok nullok md5
session required  pam_unix.so
```

See Also

[pam.conf\(5\)](#), [pam.d\(5\)](#), [pam\(8\)](#)

Author

pam_unix was written by various people.

Referenced By

[pam_pwquality\(8\)](#), [unix_update\(8\)](#)

Source: https://linux.die.net/man/8/pam_unix